§ 160.151-47

liferafts, except for items of equipment that are readily available;

- (p) A means for load-testing davitlaunched liferafts, unless the facility services only non-davit-launched liferafts:
- (q) A supply of parts for all inflation components and valves specified in the applicable manual; and
- (r) A tool board that clearly indicates where each small tool is stored, or has an equivalent means to make sure that no tools are left in the liferaft when repacked.

§ 160.151-47 Requirements for owners or operators of servicing facilities.

To maintain Coast Guard approval, the owner or operator of each servicing facility approved by the Coast Guard must—

- (a) Ensure that servicing technicians have received sufficient information and training to follow instructions for changes and for new techniques related to the inflatable liferafts serviced by the facility, and have available at least one copy of each manufacturer's approved servicing manual, revision, and bulletin;
- (b) Calibrate each pressure gauge, mechanically-operated barometer, and weighing scale at intervals of not more than 1 year, or in accordance with the equipment manufacturer's requirements:
- (c) Ensure that each liferaft serviced under the facility's Coast Guard approval is serviced by or under the direct supervision of a servicing technician who has completed the requirements of either §160.151–39 (a) or (b);
- (d) Ensure that each liferaft serviced under the facility's Coast Guard approval is serviced in accordance with the approved manual;
- (e) Specify which makes of liferafts the facility is approved to service when representing that the facility is approved by the Coast Guard; and
- (f) Ensure that the facility does not service any make of liferaft for an inspected vessel of the U.S. or any other U.S.-flag vessel required to carry approved liferafts, unless the facility is approved by the Coast Guard to service that make of liferafts.

§ 160.151-49 Approval of servicing facilities at remote sites.

A servicing facility may be approved for servicing liferafts at a remote site, provided that appropriate arrangements have been made to ensure that each such site meets the requirements of §§ 160.151-41(e), 160.151-43, and 160.151-45. The facility must have a portable assortment of test equipment, spare parts, and replacement survival equipment to accompany the technician doing the servicing. However, if repair of liferafts will not be attempted at a remote site, equipment needed for repair does not need to be available at that site. A facility must be specifically authorized in its letter of approval to conduct servicing at a remote

§ 160.151-51 Notice of approval.

If the cognizant OCMI determines that the servicing facility meets the applicable requirements of §§ 160.151-39 through 160.151-47, the OCMI notifies the facility that it is approved and notifies the Commandant. The Commandant issues an approval letter to the servicing facility with copies to the OCMI and to the manufacturer(s) whose liferafts the facility is approved to service. The letter will specify any limits on the approval, and will assign the facility's approval code for use on the inspection sticker required by $\S 160.151-57(m)(3)$. The Commandant will maintain a current list of approved facilities.

§ 160.151-53 Notice to OCMI of servicing.

- (a) Before servicing an inflatable liferaft under the servicing facility's Coast Guard approval, the owner or operator of the facility must tell the cognizant OCMI for each liferaft to be serviced—
 - (1) The make and size of the liferaft;
 - (2) The age of the liferaft; and
- (3) Whether the liferaft is due for a five-year inflation test.
- (b) The OCMI will inform the servicing facility whether the servicing of the liferaft must be witnessed by an inspector.
- (c) If the OCMI requires the servicing of the liferaft to be witnessed by an inspector—